

COP 3223 Sec 2: Spring'14 C Progr Practice Test 1 (50 points)

- 1. (7 points)

Write down the printed output of this program. Mark your blank chars too.

WRITE YOUR OUTPUT BELOW HERE
ONLY THIS WILL BE GRADED

```
#include <stdio.h>
int main(void)
{
    float f;
    int a,i;
    a = 4;
    a = a - 1;
    printf ("P= %d\n", a);
    a += 2;
    a++;
    a = a % 2;
    printf ("Q= %4d\n", a);
    i=2;
    f=13.0;
    printf ("R= %6.2f\n", f/i);
    a=13;
    printf ("S= %d\n", a/i);
    return 0;
}
```

Out Line 1 |

Out Line 2 |

Out Line 3 |

Out Line 4 |

Out Line 5 |

Out Line 6 |

- 2. (11 points) Trace the following program:

IF YOU WISH, YOU CAN ENTER YOUR TRACE BELOW

	Prog Line #	a	b	c	print or other action
1.	#include <stdio.h>				
2.					
3.	int main(void)				
4.	{				
5.	int a=5 , b=3, c=4;				
6.	a += 1;				
7.					
8.	if (b > c)				
9.	printf ("a= %d\n", a+4);				
10.	else				
11.	printf ("b= %d\n", b);				
12.					
13.	b -= 2;				
14.	if (a <= b)				
15.	{				
16.	printf ("c= %d\n", a+c);				
17.	}				
18.	else				
19.	{				
20.	if (b > c)				
21.	printf ("d= %d\n", a+c);				
22.	else				
23.	printf ("f= %d\n", c);				
24.	}				
25.					
26.	return 0;				
27.	}				

WE GRADE ONLY YOUR FINAL OUTPUT BELOW

Outline 1					
Outline 2					
Outline 3					
Outline 4					

- 4. (14 points) Write a complete C program that uses a FOR-loop to read in 50 integers. For each of the 50 integers, if it is greater than 100, it should be added into a sum that was initialized to zero. After the loop, multiply the sum by 85 and then print out the answer. Assume correct input.
- 5. (14 points) Write a complete C program that uses a FOR-loop to read in 41 integers. For each of the 41 integers, first multiply the integer by itself; if the result obtained (i.e., the squared value) is greater than 500, the original integer (before it was squared) should be added into a sum that was initialized to zero. After the loop, multiply the sum by itself and then print out the answer as an integer. Assume correct input.
- 6. (14 points) Write a complete C program that uses a FOR-loop to read in 10 integers. For each of the 10 integers, the program first multiplies the integer by 10, if the result obtained (i.e., after multiplying by 10) is greater than 85, the integer (as it was read in, i.e., before it was multiplied) should be added into a sum that was initialized to zero. After the loop is completed, multiply the sum by 100 and then print out the answer. Assume correct input. You **do not need to** include the `stdlib` or `system("pause")` statements.

For example, if the input from the keyboard is:

1 2 3 4 5 6 7 8 9 10

we expect the final outputted answer to be: 1900

- 7. (14 points) Write a complete C program that uses a FOR-loop to read in 10 positive integers. For each of the 10 integers, if the integer is divisible by 5, the integer should be added into a sum that was initialized to zero. After the loop is completed, multiply the sum by 100 and then print out the answer. Assume correct input. You **do not need to** include the `stdlib` or `system("pause")` statements.

For example, if the input from the keyboard is:

11 12 13 14 15 16 17 18 19 20

we expect the final outputted answer to be: 3500